



**BATTLE**  
M O T O R S

# REFUSE-HEIL SIDE LOADER

## PERFORMANCE AND SPECIFICATIONS

<b>GVWR</b> Up to 66,000 lbs	<b>Operating Range*</b> UP to 210 miles	<b>Top Speed</b> Up to 70 mph	<b>Wheelbase</b> Up to 248 inches
<b>Gradeability</b> Start full laden on 25%	<b>ePTO</b> 700VDC	<b>Suspension</b> Front: Taper Leaf Rear: Walking Beam or Air Ride	<b>Brakes</b> Bendix Air Disk
<b>Axles</b> Dana	<b>Cab Width</b> 82 or 94 inches	<b>Cab Configuration</b> LET II, RH, Drive Only, Tilt / Telescopic Column 12v Cab Tilt Assist Pump	<b>Cab Construction</b> Fully welded & eCoat galvanneal cab with 16GA skins

## BATTERY AND CHARGING

<b>Battery Pack</b> CATL Battery Pack (400 KW/hr)	<b>Charging Time</b> 220V 80A AC Charger: 21 hrs 150kW DC Fast Charger: <3 hrs	<b>Braking</b> Multimode Regenerative	<b>Braking Energy</b> 5% - 35% of brake energy regenerated back into Energy Storage System (depending on cycle)
---	--	---	---

## DRIVE TRAIN

<b>Motor</b> Cascadia, HVH410-150	<b>Peak Power</b> Peak: 500hp Continuous: 310hp	<b>Transmission</b> ieDrive, 2-Speed	<b>Output Torque</b> Peak: 7,834+ lbs./ft Continuous: 4,588+ lbs./ft
--------------------------------------	---	---	--



**Buy the Battle Motors fully electric Refuse: Side Loader on Sourcewell today.**  
Save time and money by purchasing your next Battle Motors truck using our ready-to-use, competitively solicited contract with Sourcewell.

\*Electric drive range varies with route, drive cycle, external conditions, configurations and driver behavior. Precise data available upon evaluation of fleet specifications.